

Uitwendige draad

Diameter	Draad maat	Draad type	Type dichting	Berkel Industrial codering
9,70	1/8"	BSPT	Conische draad	MBSPT
9,73	1/8"	BSPP	60° holconus	MBSP
10,29	1/8"	NPT	Conische draad	MNPT
11,11	7/16"	UNF	74° bolconus	MJ (JIC)
12,00	M12x1,5	Metrisch	24° holconus	EFAL / EFAF
12,70	1/2"	UNF	74° bolconus	MJ (JIC)
13,16	1/4"	BSPP	60° holconus	MBSP
13,20	1/4"	BSPT	Conische draad	MBSPT
13,72	1/4"	NPT	Conische draad	MNPT
14,00	M14x1,5	Metrisch	24° holconus	EFAL / EFAF
14,29	9/16"	UNF	74° bolconus	MJ (JIC)
14,29	9/16"	UNF	vlak	MORFS
16,00	M16x1,5	Metrisch	24° holconus	EFAL / EFAF
16,60	3/8"	BSPT	Conische draad	MBSPT
16,66	3/8"	BSPP	60° holconus	MBSP
17,15	3/8"	NPT	Conische draad	MNPT
17,50	11/16"	UNF	vlak	MORFS
18,00	M18x1,5	Metrisch	24° holconus	EFAL / EFAF
19,05	3/4"	UNF	74° bolconus	MJ (JIC)
20,60	13/16"	UNF	vlak	MORFS
20,80	1/2"	BSPT	Conische draad	MBSPT
20,96	1/2"	BSPP	60° holconus	MBSP
21,34	1/2"	NPT	Conische draad	MNPT
22,00	M22x1,5	Metrisch	24° holconus	EFAL / EFAF
22,23	7/8"	UNF	74° bolconus	MJ (JIC)
22,90	5/8"	BSPT	Conische draad	MBSPT
22,91	5/8"	BSPP	60° holconus	MBSP
25,40	1"	UNF	vlak	MORFS
26,00	M26x1,5	Metrisch	24° holconus	EFAL / EFAF
26,40	3/4"	BSPT	Conische draad	MBSPT
26,44	3/4"	BSPP	60° holconus	MBSP
26,67	3/4"	NPT	Conische draad	MNPT
26,99	1-1/6"	UNF	74° bolconus	MJ (JIC)
30,00	M30x2	Metrisch	24° holconus	EFAL / EFAF
30,16	1-3/16"	UNF	74° bolconus	MJ (JIC)
30,16	1-3/16"	UNF	vlak	MORFS
33,20	1"	BSPT	Conische draad	MBSPT
33,25	1"	BSPP	60° holconus	MBSP
33,34	1-5/16"	UNF	74° bolconus	MJ (JIC)
33,40	1"	NPT	Conische draad	MNPT
36,00	M36x2	Metrisch	24° holconus	EFAL / EFAF
36,50	1-7/16"	UNF	vlak	MORFS
39,00	1-1/4"	BSPT	Conische draad	MBSPT
41,28	1-5/8"	UNF	74° bolconus	MJ (JIC)
41,91	1-1/4"	BSPP	60° holconus	MBSP
42,16	1-1/4"	NPT	Conische draad	MNPT
42,90	1-11/16"	UNF	vlak	MORFS
44,80	1-1/2"	BSPT	Conische draad	MBSPT
45,00	M45x2	Metrisch	24° holconus	EFAL / EFAF
47,63	1-7/8"	UNF	74° bolconus	MJ (JIC)
47,80	1-1/2"	BSPP	60° holconus	MBSP
48,26	1-1/2"	NPT	Conische draad	MNPT
50,80	2"	UNF	vlak	MORFS
52,00	M52x2	Metrisch	24° holconus	EFAL / EFAF
59,60	2"	BSPT	Conische draad	MBSPT
60,33	2"	BSPP	60° holconus	MBSP
60,33	2"	NPT	Conische draad	MNPT
63,50	2-1/2"	UNF	74° bolconus	MJ (JIC)

Inwendige draad

Diameter	Draad maat	Draad type	Type dichting	Berkel Industrial codering
8,57	1/8"	BSPP	60° bolconus	TBSP
8,57	1/8"	NPT	Conische draad	
8,60	1/8"	BSPT	Conische draad	
9,74	7/16"	UNF	74° holconus	TJ (JIC)
10,50	M12x1,5	Metrisch	24° bolconus	ETALO / ETAFO
11,27	1/4"	NPT	Conische draad	
11,33	1/2"	UNF	74° holconus	TJ (JIC)
11,45	1/4"	BSPP	60° bolconus	TBSP
11,50	1/4"	BSPT	Conische draad	
12,50	M14x1,5	Metrisch	24° bolconus	ETALO / ETAFO
12,76	9/16"	UNF	vlak	TORFS
12,76	9/16"	UNF	74° holconus	TJ (JIC)
14,50	M16x1,5	Metrisch	24° bolconus	ETALO / ETAFO
14,70	3/8"	NPT	Conische draad	
14,95	3/8"	BSPP	60° bolconus	TBSP
15,00	3/8"	BSPT	Conische draad	
15,90	11/16"	UNF	vlak	TORFS
16,50	M18x1,5	Metrisch	24° bolconus	ETALO / ETAFO
17,33	3/4"	UNF	74° holconus	TJ (JIC)
18,16	1/2"	NPT	Conische draad	
18,60	1/2"	BSPT	Conische draad	
18,63	1/2"	BSPP	60° bolconus	TBSP
19,10	13/16"	UNF	vlak	TORFS
20,26	7/8"	UNF	74° holconus	TJ (JIC)
20,50	M22x1,5	Metrisch	24° bolconus	ETALO / ETAFO
20,59	5/8"	BSPP	60° bolconus	TBSP
20,60	5/8"	BSPT	Conische draad	
23,80	1"	UNF	vlak	TORFS
24,10	3/4"	BSPT	Conische draad	
24,12	3/4"	BSPP	60° bolconus	TBSP
24,50	M26x1,5	Metrisch	24° bolconus	ETALO / ETAFO
24,70	1-1/6"	UNF	74° holconus	TJ (JIC)
27,87	1-3/16"	UNF	vlak	TORFS
27,87	1-3/16"	UNF	74° holconus	TJ (JIC)
27,90	M30x2	Metrisch	24° bolconus	ETALO / ETAFO
29,52	1"	NPT	Conische draad	
30,29	1"	BSPP	60° bolconus	TBSP
30,30	1"	BSPT	Conische draad	
31,05	1-5/16"	UNF	74° holconus	TJ (JIC)
32,51	3/4"	NPT	Conische draad	
33,90	M36x2	Metrisch	24° bolconus	ETALO / ETAFO
34,10	1-7/16"	UNF	vlak	TORFS
38,25	1-1/4"	NPT	Conische draad	
38,95	1-1/4"	BSPP	60° bolconus	TBSP
38,98	1-5/8"	UNF	74° holconus	TJ (JIC)
39,00	1-1/4"	BSPT	Conische draad	
40,40	1-11/16"	UNF	vlak	TORFS
42,90	M45x2	Metrisch	24° bolconus	ETALO / ETAFO
44,32	1-1/2"	NPT	Conische draad	
44,80	1-1/2"	BSPT	Conische draad	
44,85	1-1/2"	BSPP	60° bolconus	TBSP
45,33	1-7/8"	UNF	74° holconus	TJ (JIC)
48,30	2"	UNF	vlak	TORFS
49,90	M52x2	Metrisch	24° bolconus	ETALO / ETAFO
56,36	2"	NPT	Conische draad	
56,66	2"	BSPP	60° bolconus	TBSP
59,70	2"	BSPT	Conische draad	
61,21	2-1/2"	UNF	74° holconus	TJ (JIC)